



FyreWrap® XFP® Expanding Paper Insulation & Fire Protection Systems

Home / FyreWrap Duct Insulation & Fire Protection Products / FyreWrap XFP Expanding Paper Insulation & Fire Protection System



FyreWrap® Fire Protection Solutions For Global Markets
FyreWrap® is a registered product of Unifrax I LLC
On the web at: <http://www.unifrax.com>

FyreWrap® XFP® Expanding Paper

FyreWrap® XFP® Expanding Paper is a flexible, lightweight, high temperature intumescent mat that expands up to three times in thickness in the event of a fire. FyreWrap XFP Paper is used in fire resistant applications, to fill cracks or voids and prevent the spread of flames, heat, and smoke.

FyreWrap XFP Expanding Paper is available in various forms:

- **FyreWrap XFP**, plain intumescent mat
- **FyreWrap XFP-A**, laminated with 0.003" aluminum foil on one face
- **FyreWrap XFP-S**, laminated with 0.002" stainless steel foil on one face

FyreWrap XFP Expanding Paper is a composite material comprised of 30-45% **Fiberfrax** refractory ceramic fiber, 45-60% unexpanded vermiculite, and 5-9% organic binder system.

FyreWrap XFP Expanding Paper is available in various sizes:

- Thickness: 0.10in, 0.15in, 0.20in, or 0.25in
- Width: 24in or 49in
- Length: 20.5ft, 25ft, or 50ft

Downloadable PDF Documents:

FyreWrap XFP Expanding Paper Product Information Sheet
FyreWrap XFP Expanding Paper MSDS M0197
UPDATED FyreWrap MSDS M0197 From www.Unifrax.com

FyreWrap XFP Expanding Paper fits within a range of fiber insulation products that allows [Unifrax](http://www.unifrax.com) to be your single source supplier for all high temperature insulation and fire protection specifications.

If you need technical advice regarding **FyreWrap XFP Insulation & Fire Protection System** applications in the US or CANADA, e-mail info@unifrax.com or Call (716) 278 3800.

For INTERNATIONAL **FyreWrap Product** applications please find your location in the **Unifrax International Sites table** and click on the most appropriate image to link to your local **Unifrax Center of Expertise**.

FyreWrap® XFP® Expanding Paper Intumescent Mat



Expansion Temp: 620°F (327°C)
Expansion Ratio: 3:1

*Expansion Plugs Heat/Fire Paths
High Temperature Stability
Low Thermal Conductivity
High Thermal Reflectivity
Superior Flexural Integrity
Effective Moisture Barrier*



FyreWrap Fire Protection Products Customer Service Dept.
Unifrax Corporate Headquarters
2351 Whirlpool Street
Niagara Falls, NY, 14305-2413, USA
Tel: (716) 278 3800, Fax: (716) 278 3900
e-mail: info@unifrax.com
web: <http://www.unifrax.com>

FyreWrap® and Fyrewrap® XFP® Expanding Paper are registered trademarks of Unifrax I LLC

Contact Unifrax to find out more about the optimum high temperature insulation and fire protection products for Your particular industrial process or commercial application

FyreWrap.com Links & pdf's:

- Fyrewrap Home (pdf)
- Fyrewrap Product Forms: (pdf)
 - FyreWrap Elite 1.5 Duct Insulation (pdf)
 - FyreWrap 1.5 & 2.0 Cable Insulation (pdf)
 - FyreWrap 0.5 Plenum Insulation (pdf)
 - FyreWrap XFP Expanding Paper (pdf)
 - Fyrewrap Marine Blanket Insulation (pdf)
 - Fyrewrap Rail Tank Car Insulation (pdf)